

PK73.222B1

10.1" HD Camera Kit - Multiple view

NBS Cam

Avoid blind spots!



Characteristics

- ✦ 10.1 " touchscreen color digital display (1080P)
- ✦ Multiple view monitor, 4 channels
- ✦ Single, dual, triple, quad, trefoil display
- ✦ camera inputs, 1 video input
- ✦ Built-in microphone and speaker
- ✦ Camera housing heating under 10°C
- ✦ Brightness automatic adjustment Day / night
- ✦ 1 year warranty
- ✦ Cable: 5m, 10m, 15m, 20m (option)

Specifications

Camera

CH100

Image Device:	Color CCD
Housing:	Heating (under 10 ° C)
Lens angle:	120°
Waterproof:	IP69K
Operating Temperature:	-30 to +70°C
Storage Temperature:	-40 to +70°C
Power source:	12-24 VDC
Resolution:	600 TV line
Array size:	976x494 pixels
Night vision distance:	12-15m (IR-CUT)
Picture image:	Normal / Mirror
Audio:	Built-in microphone
Material:	Ionized aluminum
TV system:	PAL / NTSC
Connection:	RCA / 4 pins
Anti-vibration	10g
Certification:	CE, EMARK, FCC
Weight (lbs / kg):	1.23 / 0.56
Size (cm):	11.6x8.5x7.9

Monitor

MH991*

Size:	10.1"
Type:	Touchscreen - Color LCD
Picture image:	Multiple
Number of channel:	4
Operating Temperature:	-20 to +70°C (RH90%)
Storage Temperature:	-30°C to + 80°C (RH90%)
Power source:	12-24 VDC
Resolution:	1024x3 (RGB) x 600
DOT pitch:	0.2175 (W) x 0.2088 (H)
Brightness:	500 cd/m2
Contrast:	600: 1
Audio:	Built-in speaker (1.5W)
Power consumption::	Max 25W
Viewing angle:	U: 70° D: 50° R/L: 70° / 70°
Anti vibration:	3g (center mount bracket) / 7g (U support)
Weight (lbs / kg):	4.54 / 2.6
Outside sizes (mm):	267 (W) x 159.5 (H) x 30 (T)

* 7" monitor available - MH964