

PK77.231A

AI100 camera kit - Pedestrian Detection

NBS Cam

Avoid blind spots!



Characteristics

- ✦ Pedestrian and cyclist detection
- ✦ Detection range 0.5-20M adjustable
- ✦ Adjustable color stripes to show detected areas;
- ✦ No control box needed, can be directly connected to normal monitors or DVR.
- ✦ Camera housing heating under 10°C
- ✦ Waterproof/dustproof rating: IP69K
- ✦ 1 year warranty

Specifications

Camera

AI100

Waterproof:	IP69K
Operating Temperature:	-20 to +70°C
Storage Temperature:	-30 to +80°C
Power source:	12-24 VDC
Resolution:	1920x1080P
Video output:	AHD(1.0Vp-p, 75ohm)
Audio output:	Yes
Viewing angle:	52°(Horizontal); 60°(Diagonal)
Communication Interface:	USB 2.0 (For Software upgrading)
Vibration Resistance:	5.9G
Dimension (mm):	95x60x70
Frame Rate:	25 or 30

Kit available

PK77.231A1:	1 monitor, 1 camera
PK77.231A2:	1 monitor, 2 cameras
PK77.231A3:	1 monitor, 3 cameras
PK77.231A4:	1 monitor, 4 cameras

* Cables are always ordered separately

Moniteur

MH991*

Size:	10.1"
Type:	Touchscreen - Color LCD
Picture image:	Multiple
Number of channel:	4
Operating Temperature:	-20 to +70°C (RH90%)
Storage Temperature:	-30°C to + 80°C (RH90%)
Power source:	12-24 VDC
Resolution:	1024x3 (RGB) x 600
DOT pitch:	0.2175 (W) x 0.2088 (H)
Brightness:	500 cd/m2
Contrast:	600: 1
Audio:	Built-in speaker (1.5W)
Power consumption::	Max 25W
Viewing angle:	U: 70° D: 50° R/L: 70° / 70°
Anti vibration:	3g (center mount bracket) / 7g (U support)
Weight (lbs / kg):	4.54 /2.6
Outside sizes (mm):	267 (W) x 159.5 (H) x 30 (T)

* 7" monitor available - MH964