## PK73.010E1

7" HD Camera Kit- Single view



Avoid blind spots!



## **Characteristics**

- # 7 " touchscreen color digital display (1080P)
- Single view monitor, 1 channels
- Built-in microphone and speaker
- # 120° field of view
- Camera housing heating under 10°C
- Brightness automatic adjustment Day / night
- 4 1 year warranty
- + Cable: 5m, 10m, 15m, 20m (option)

## **Specifications**

Camera	CH100
Image Device:	Color CCD
Housing:	Heating (under 10 ° C)
Lens angle:	120°
Waterproof:	IP69K
Operating Temperature:	-30 to +70°C
Storage Temperature:	-40 to +70°C
Power source:	12-24 VDC
Resolution:	600 TV line
Array size:	976x494 pixels
Night vision distance:	12-15m (IR-CUT)
Picture image:	Normal / Mirror
Audio:	Built-in microphone
Material:	Ionized aluminum
TV sytem:	PAL / NTSC
Connection:	RCA / 4 pins
Anti-vibration	10g
Certification:	CE, EMARK, FCC
Weight (lbs / kg):	1.23 / 0.56
Size (cm):	11.6x8.5x7.9

Monitor	MH727*
Size:	7"
Туре:	Touchscreen - Color LCD
Picture image:	Single
Nomber of channel:	1
Operating Temperature:	-20°C to +70°C (RH90%)
Storage Temperature:	-30°C to + 80°C (RH90%)
Power source:	12-24 VDC
Resolution:	1024x3 (RGB) x 600
DOT pitch:	0.1506 (W) x 0.1432 (H)
Brightness:	700 cd/m2
Contrast:	800: 1
Audio:	Built-in speaker (1.5W)
Power consumption:	Max 10W
Angle de visualisation:	U: 85° D: 85° R/L: 85°/ 85°
Anti vibration:	3g (center mount bracket) / $7g$ (U support)
Weight (lbs / kg):	3.53 /1.6
Outside sizes (mm):	182 (W) x 122 (H) x 28.7 (T)